









Size:- 200x200mm











Note:-

All Color's Available in 100x300mm & 200x200mm Size.



SPECIFICATION

CHARACTERISTICS	EURO STANDARD	OUR VALUE			
DIMENSION & SURFACE QUALITY					
DIMENSION & SURFACE QUALITY DEVIATION IN THICKNESS STRAIGHTNESS OF SIDES RECTANGULARITY SURFACE FLATNESS SURFACE QUALITY	± 0.5% ± 0.6mm ± 0.3% ± 0.5% ± 0.5% MIN 95%	± 0.2% ± 0.2mm ± 0.2% ± 0.3% ± 0.3% MIN 96%			
PHYSICAL PROPERTIES					
WATER ABSORPTION BEND STRENGTH SCRATCH HARDNESS (MOHS) CRAZ I NG	> 10% > 150Kg _* /cm² MIN 3 1 CYCLE	> 14 - 17 % > 200-250kg./cm² MIN 3 NO CRAZING AT 2 CYCLE			
CHEMICAL PROPERTIES					
STAINING RESISTANCE HOUSEHOLD CHEMICAL	MIN CLASS 2 MIN CLASS B	RESISTANCE TO ALL ACIDS AND ALKALIES & HOUSEHOLD CHEMICALS EXCEPT HYDRO FLURIC ACID			
THERMAL PROPERTIES					
THERMAL SHOKE THERMAL EXPANSION	RESISTANT TO 10 CYCLE MAX-9E-06	CONFORMS CONFORMS			

PACKING DETAIL

Dimension (mm)	Tile Per Box (pcs)	Area Coverage per Box (Sq. ft.)Approx	Area Coverage per Box (Sq. m.)Approx	Weight per Box (Kg.)Approx
200 x 200 mm	25	10.76	1.00	10.500
100 x 300 mm	33	10.66	0.99	13.000

Note: Size / shade variation is inherent in ceramic tiles, in case of any complain its should be brought to our dealer's notice before laying the tiles. colour shown are indicative only. Check actual tiles for exact colour.

The information contained in this catalogue are accurate as possible, but cannot be considered as legally binding.

Customers are advised to inspect a sample of the tile before ordering.

The company reserves the right to change the specifications without prior notice.



















